



Photo Emission Tech., Inc.

760 Calle Plano, Camarillo, CA 93012 USA

Tel: (805) 482-5200 Fax: (805) 482-5252

Email: pet@photoemission.com

SHUNTED REFERENCE CELLS

GENERAL INFORMATION

Reference cells are most commonly used for measuring and setting the intensity of solar simulators for one sun (or other user desired) intensity condition. They can also be used (with supporting equipment) to measure the temporal stability and/or non-uniformity of the light beam of solar simulator.

FEATURES

- ❖ Rugged aluminum black anodized enclosure for stability
- ❖ 20mm x 20mm Silicon solar cell
- ❖ BK7 Window
- ❖ Mounting hole pattern (62mm x 62mm) compatible with WPVS reference cell design
- ❖ Shunted inside the body with an appropriate size resistor, thus giving an output voltage usually between 50mV to 60mV for an irradiance of 1,000W/m²
- ❖ Cable length one (1) meter with Banana Plug to connect directly to a Digital Volt Meter.

OPTIONS

- ❖ Quartz window instead of BK7
- ❖ Custom cells incorporating special cells from customer, thus assuring a much better match between reference cells and production cells. This also helps in minimizing spectral response mismatch or errors
- ❖ RTD temperature sensor
- ❖ Cable termination of customer's choice
- ❖ Different size solar cell or aperture placed over solar cell