



Photo Emission Tech., Inc.
862 Patriot Drive Unit F, Moorpark, CA 93021 USA
Tel: (805) 482-5200 Fax: (805) 482-5252
Email: pet@photoemission.com

SOLAR SIMULATORS MODEL # SS50AAA

SS50AAA-EM ELECTRO-MECHANICAL SYSTEM FEATURES

- Light intensity feedback for stable output intensity
- **Electro-Mechanical Controller**
- Lamp life display
- External lamp alignment with lamp on
- Manual/Automatic/External/Remote shutter control
- Forced air cooling
- Lamp Life Meter
- Lamp Current Meter
- Selectable and adjustable constant intensity or constant power mode
- Safety Interlock override LED
- Over Temperature Warning LED
- Shutter Status Indicator
- Lamp status indicator
- One (1) year factory warranty



STANDARD ELECTRO-MECHANICAL (EM) SYSTEM

Specifications are subject to change without notice.



Photo Emission Tech., Inc.
862 Patriot Drive Unit F, Moorpark, CA 93021 USA
Tel: (805) 482-5200 Fax: (805) 482-5252
Email: pet@photoemission.com

SOLAR SIMULATORS MODEL # SS50AAA

SS50AAA-TP TOUCH PANEL SYSTEM FEATURES

- Light intensity feedback for stable output intensity
- **Computer based Controller**
- Manual / automatic shutter control
- External lamp alignment with lamp on
- Manual/Automatic/External/Remote shutter control
- Forced air cooling
- Lamp life display
- Selectable and adjustable constant intensity or constant lamp current
- Safety Interlock override warning
- Shutter Status Indicator
- Lamp status indicator
- **Remote Trouble Shooting via Internet**
- One (1) year factory warranty



OPTIONAL TOUCH PANEL (TP) SYSTEM

Specifications are subject to change without notice



Photo Emission Tech., Inc.

862 Patriot Drive Unit F, Moorpark, CA 93021 USA

Tel: (805) 482-5200 Fax: (805) 482-5252

Email: pet@photoemission.com

CELL TESTER MODEL # SS50AAA

SS50AAA-TP & SS50AAA-EM TECHNICAL SPECIFICATIONS

FEATURE DESCRIPTION	SPECIFICATION
Type of lamp	Xenon Short Arc
Lamp Power	150 W
Max. Illuminated area	2" (50mm) X 2" (50mm)
Light Source	Steady State
Air Mass	AM1.5G Standard: AM1.5D or AM1 optional
Lamp lifetime	1,500 Hours
Adjustment Range of light intensity	100 mW/cm ² +/- 15%
Typical Spectral Range	250nm - >2,200nm
Simulator Class*	AAA
Spectral Match to all intervals*	±25% or better
Spatial Non-uniformity of irradiance*	≤ 2% or better
Short Term Temporal Instability (STI)*	≤ 0.5% or better
Long Term Temporal Instability (LTI)*	≤ 2% or better
Dimensions (Height x Width x Depth)	28.5" (724mm) x 10.4" (264mm) x 15.9" (404mm)
Weight	65 Lbs. (29.5 Kg)
Optimum Working Distance	4.6" (117mm)
Phase/Voltage/Frequency	Single Phase/110-220AC Volts/50-60Hz
Max. Power Consumption (W)	0.5 KVA

*MEETS CLASS A REQUIREMENTS OF ASTM E927-2010, IEC60904-9 Edition 2.0 2007-10 and JIS C 8912-1998: amendment 1-2005 & Amendment 2-2011